



Combination of natural linseed oil and vegetable wax emulsion to protect untreated oak against (acid) rain, air pollution and algae growth.

PRODUCT DESCRIPTION

This oil gives your wood a matt, rustic look with excellent water repellency. The oil allows the wood to breathe. The oil protects the surface against green deposits and air pollution. The wood becomes slightly grey over the years.

TECHNICAL DATA

- Appearance: dirty white liquid
- Odour: faint washing smell
- Density: 1
- Viscosity: 25"/DIN 4mm.
- PH: 8.4
- Shelf life: 2 years in a sealed container

PREPARATION

The surface must be untreated, cleaned and sanded (grit 120). If working on old wood, carefully remove the old layers first.

INSTRUCTIONS FOR USE

- Stir very well before use, and also regularly during use
- Apply undiluted with a brush or roller
- For untreated surfaces, treat at least twice. If the surface continues to absorb, it is advisable to continue the treatment until the surface is saturated
- The number of layers can affect the gloss slightly
- All materials used for application can be cleaned with water.

CURING TIMES

Dust dry after 4 hours, second coat after 24 hours.

PRACTICAL COVERAGE

Inducoat B.V. – Spacelab 17A – 3824MR – AMERSFOORT – www.Inducoat.com – (033) 456 23 94 – info@Inducoat.com

10 m²/liter depending on the suction power of the surface.

MAINTENANCE

It is recommended to treat untreated wood at least twice. When the surface loses its water-repellent properties, it is recommended to treat it again. We recommend maintaining the outdoor wood every three years with OAKPROTECT.

PACKAGING AND STORAGE

- Packaging: 2.5 L Tin (large pack available on request)
- Shelf life: 2 years in closed packaging
- Dry and frost-free storage
- Keep out of reach of children

SAFETY

The oil wax is completely natural, free of solvents and therefore does not require any special safety regulations. However, we always advise to take note of the safety data sheet.