



INDUCOAT[®]

Ecological

Fills the pores of the stone (suitable for almost all types of stone) so that rainwater, air pollution and especially algae and moss cannot adhere to the surface for a long time.

TYPES OF STONE

Suitable for mineral surfaces such as:

Limestone, Sandstone, Arduin, Marble, Stones, Cement stones, Terracotta. Especially suitable for bluestone:

Stone protection provides colour retention and protects against UV.

PROPERTIES

- Fully breathable - vapour permeable
- Non-film forming - virtually invisible
- Fully water based - 0% solvents
- Appearance: Milky liquid
- Density: 1.06
- Viscosity: 12"/DIN.4mm
- PH value: 9.4
- Odor: Faint laundry odor
- Discolouration: None

PREPARATION

Before application, clean the surface with high pressure, steam and the Inducoat CLEANER.

PACKAGE AND STORAGE

- Packaging: 5L Jerrycan, also a 1 liter spray available
- Shelf life: 2 years in closed packaging
- Dry and frost-free storage

APPLICATION

The product is immediately ready for use. The jerrycan must be shaken well for a few minutes to create a homogeneous liquid. After shaking, let the impregnating wax rest for a few minutes. Large surfaces can be given the first coat with a low-pressure sprayer - spray crosswise so that the entire surface is actually covered. Then use a block brush or roller to close the pores ensuring the surface is completely and evenly filled. The advice is to apply at least 2 layers. Apply each layer in an identical manner. After each layer, assess whether the stone has absorbed the material well; STONEPROTECT is absorbed into the surface. Also keep a close eye on the surface temperature. After evaporation the water leaves the impregnated surface with a layer of natural wax.

- Dust dry: 30 minutes
- Fully cured: after 24 hours at relative humidity of 60%
- Application temperature: 5-200 Celsius – Do not use in full sun on surfaces that are too warm
- Practical efficiency: Layer 1 = 5-10m² / Layer 2 = 10-20m²
- Application method: Block brush, roller, airless
- Cleaning: Water
- Removal: Easily removable with alkaline Inducoat Ecological REMOVER

SAFETY

The impregnating wax is completely natural, free of solvents and therefore does not require any special treatment safety regulations. We always recommend that you take note of the safety data sheet. Keep out of reach of children